

Technical Data Sheet

Material composition	Recycled granulate bound using a PU binding agent and possibly a colouring agent.
Size	600 x 1200mm
Thicknesses	30mm
Weight	20kg per tile approximately
Colours	Black with coloured EPDM edges
Density	800 kg/m ³
Fire resistance	Efl to EN 13501
Smoke resistance	S2
TÜV	WalkwayPro rubber tiles are TÜV certified. They meet the Attractions and Playground Apparatus Act EN1177 Size tolerance: width 2% and thickness 5%
Colour	The black recycled body of the product is not colour fast and the colour may change due to influences of the weather and walking on the tiles.
Carbon black	Carbon black is a black colouring agent which exists in every rubber tile and which can come out due to influences of the weather. Quicklime/cement veiling: due to weather influences and quicklime/cement veiling of the surrounding objects the tiles and mats might develop a white efflorescence.
Guarantee	5 year guarantee for wear-resistance, with the exception of tiles that are used intensively. The guarantee does not apply to the colour of the black recycled areas of the tile.
Recycling	Products are 100% recyclable.
Water permeability	350 mm per hour EN 12616
Slip Resistance	Dry:102 Wet:62 (Low Potential For Slip) As Per EN 1339:2003 Pendulum Tester
Insulation Value	Rd 0,15 EN 13165, U 3,13 EN6946